

Conor Nova Smart Bidet Seat Manual


Model

CR-NR

Thanks for choosing our product

And please read the instructions carefully before using.

The pictures are for reference only, please refer to the actual product



WaterMark
WMTS-051
WM-022574



Contents

Before use

Safety precautions	1
Overall sketch	6
Function introduction	7

Installation guide

Precautions before installation	8
Toilet Seat installation	9

Operation

Operation introduction	11
Preparation	11
Product use	12
Troubleshooting	16
Cleaning and Maintenance	17

Appendix

Product specification	19
Packing list	20

Safety precautions

Please read the “safety precautions” carefully before use, all the precautions listed here are connected to safety. It's important and must be followed.

Sign and meaning

	Warning	Represents improper operations by ignoring the instructions may result in death or injury
	Notice	Represents improper operations by ignoring the instructions may result in body injury and property loss

The following signs are used for important safety precautions.

Sign	meaning
	It represents not allowed, “forbid”
	It represents enforced to do

 WARNING	
	Please do not touch the electrical outlet with wet hand • Or it may cause electric shock Please do not pour water, hot water or detergent on the top of the toilet and electrical outlet • Or it may cause fire, electric shock, heat or short circuit • Or it may cause injury and indoor water seepage because of the damage of product Never attempt to disassemble, repair, or alter the product yourself. • Or it may cause fire, electric shock, heat or short circuit Please do not install the toilet in car, ship or any other moving object. • Or it may cause fire, electric shock, short circuit or fault. • Or the ceramic, seat and main part will be damaged because of falling down. Stop using while it breakdown Under the following condition, please disconnect the power supply and turn off the water angle valve — Water leakage from pipe or inside of the product — crack or damage on the product — unusual sound or smell — Smoke — Unusual heating — Block — Fall out of the cushion • Continue using the toilet by ignoring the faults may result in fire, electric shock, heat, short circuit, injury and indoor water seepage



WARNING



Please don't use seawater and other water except tap water or drinkable well water(underground water)

- Or it may cause skin inflammation or fault

Please do not touch the electrical plug while thunder

- Or it may cause electric shock

Please do not let the water inlet soft pipe connect to the electrical plug and outlet

- Or it may cause fire, electric shock, heat, short circuit because of moisture condensation

Please do not destroy power cable or plug

Does not strike, yank, twist, excessively bend, damage, or alter the electrical cords. Also, do not place anything heavy on, bind or pinch the cords.

- Or it may cause fire, electric shock, heat and short circuit if it's broken

Please do not use a loose or faulty electrical outlet.

- Or it may cause fire or short circuit.

Please use the electrical outlet and wire appliance in specified area.

- Or it may cause fire because of wire appliance is not in the rule of outlet.

Please do not put finger or anything else into the warm air outlet.

Please do not put objects or clothes on the air outlet or cover it.

- Or it may cause scald, electric shock or accessories burn down.

Please keep cigarettes and other open flames away from the product

- Or it may cause fire.



Pay attention to the low temp scalding

- Improper use of warm seat may cause low temp scalding.

If you sit for long time, please turn the temp setting to "off" level.

Please turn the seat temp setting to "off" level, warm air dry temp to "low" level under following situations.

- Children and elders those who can not adjust the temp to the proper level
- Patient and disabled people those who have problem in behavior.
- People who have take medicine with hypnosis effect(hypnotics, cold cure and etc), or are excessive drinking, too tired and somnolence.

This is an electrical product, please do not install it in a place where is easily get wet or with high humidity. If installed in bathroom, please also install ventilator to maintain the bathroom ventilation.

- Or it may cause fire or electric shock.

The product must be connected to cold water supply.

- Or it may cause body burn or machine fault.

The product must be connected to the ground correctly.

- If not connected to the ground, it may cause electric shock.

The ground processing here requires the ground resistance under 100Ω, the earth wire of switchboard is over Ø1.5mm, with copper material. (please entrust installation company to do the job)



WARNING

Please confirm if the electrical outlet is connected to the ground

- Or it may cause electric shock because of fault or short circuit.

The outlet for power wire should obey the following rules.

- Or it may cause fire or electric shock.
 - a. Please use high sensibility and fast respond leakage switch (rated induced currents below 15mA) or insulating transformer (1.5kVA~3kVA) to protect outlet loop.
 - b. Please reserved the installation place for outlet and keep it away form bathtub.
- * Please confirm above a , b wiring projects are finished. Or please entrust the engineering contractor to do this job.

The electrical plug should be inserted to the outlet firmly.

- Or it may cause fire, heat or short circuit.

Please hold the plug not the wire when pulling out the plug.

Please do not grasp the wire to pull out the plug.

- Or it may cause fire or heat because of broken wire.

If the power soft wire is broken, to avoid danger, please ask the maintenance department of company or similar departments to replace it.

Please be sure to turn off the power while doing the maintenance or spot check.

- Or it may cause electric shock or accessories burn down.
 - * Not include " nozzle clean"

Disabled people or who is lack of experience or common sense (including children) should be accompanied with personnel guardian while using this product.

- Or it may cause scald, electric shock, fire and body injury.

Please do not let children play this product.

- Or it may cause scald, electric shock, fire and body injury.

Do not throw lighted cigarettes and other flaming material into the toilet.

- Or it may cause fire.

Strong magnets inside, the body is equipped with a pacemaker and other auxiliary medical equipment, please do not use.





NOTICE



Please do not use the product when it's loose.

- Or the toilet and seat may separate and fall off to cause body injury

Please do not touch broken area.

- Or it may cause injury, please replace it as soon as possible.

Please do not impact forcefully, put heavy subject or stand on the product

- Or it may cause product damage, fall down or body injury
- Or it may cause body injury or indoor water seepage

Please do not pull the product by holding the seat or cover.

Please do not open the seat and cover when something on the product.

- Or the main body may fall off to cause body injury.

Please use kitchen detergent(neutral) to maintain the plastic part(seat cover, etc) and water inlet soft hose, please do not use the following materials [bathroom detergent, house detergent, gasoline, banana oil, cleaning powder and nylon brush and so on]

- Or it may damage the plastic parts, cause cracks to body injury for fault
- Or it may cause water leakage because of damaged soft hose

To avoid sudden water leakage, please do not remove the water inlet filter when angle valve is open

[please refer to cleaning instruction of water inlet filter]

- Or the water may spray out

Please do not crush or bend water inlet hose

- Or it may cause water leakage

Please use the new hose that put inside the accessory box, the old one isn't recycled.

- Or it may cause water leakage

Please do not pour hot water into toilet

- Or it may cause body injury or indoor water seepage because of toilet damage

Please do not flush with big amount of toilet paper or other subjects except sewage and small amount toilet paper.

- Or it may cause body injury or indoor water seepage because of toilet damage

Please do not lean on the toilet cover while using

- Or it may destroy the seat cover.



NOTICE



Please close the angle valve when water leaking

When room temp is under 0℃, to avoid piping or soft hose damaging because of frozen, anti freezing measures should be adopted.

- It may destroy main body or piping, leading to water leakage if water inlet soft hose is frozen.
- To avoid damage, please pay attention to room temp adjustment.

When not use for a long time, please must drain the inlet soft hose, and cut the power.

- When using next time, please open the angle valve and let water connected first. or it may cause skin inflammation because of bad water quality.
- It may cause fire or heat if the power supply is always connected.

Please must confirm if the filter has screwed to right position when install it.

- It may cause water leakage if not screwed tight.

When the toilet drain outlet is blocked, cut off the power then clean the obstruction

- Or the sewage may overflow, cause indoor water seepage because of auto flush function.
- Use the professional tools sold in the market to clean the obstruction.


Flush the toilet after pee

- Or it may cause difficulty in clean the toilet, block the drain outlet or sewage overflow, result in indoor water seepage.

Use the dried towel to clean the pee, dee, detergent, water and etc on the floor.


- Or it may leave dirt on the floor or corrode the floor.

Overall Sketch




1	Toilet lid
2	Water inlet
3	Control panel
4	Heated seat
5	Cushion pad
6	Damper
7	Dryer outlet
8	Nozzle
9	Sensing area

Install components



Waterway connection accessories



Seat fixing accessories

NOTICE

The contents described in this manual include but are not limited to product material, process, functional characteristics, etc., which may be different from the actual product due to process improvement or product upgrade. Please refer to the actual product.

Functions introductions

Function	Introduction
Rear wash	Provide rear cleansing
Rear oscillating Wash	Move the nozzle back and forth for rear cleansing
Front wash	Provide cleansing by front cleansing nozzle with a gentle spray
Front oscillating Wash	Move the nozzle back and forth with a gentle spray
Child wash	Children's special warm water gentle cleaning
One solution	Auto clean, flush and dry
Strong wash	Large amount of water to clean the buttocks to promote laxative
Lady care	Special cleaning of female's physiological period
Nozzle position adjustment	Adjust the suitable washing positions
Temperature adjustment	Set the temperature of seat and water
Water pressure adjustment	Change cleaning water pressure
Seat sensor	Functions activated by sitting on the seat
Drying	Dry the users after cleansing
Changing drying intensity	Control the temperature of warm air from the dryer
Nozzle self-clean	Provide nozzle self-cleaning before washing
Deodorizer	Removing odors
Saving energy	Saves electricity
Night light	Preparations for insufficient light
soft close	Damper in the seat and cover, to make it close softly
Power switch	Turn power on and off

Installation guide

Important Installation Notice

For safe and reliable use, this product should be installed by a licensed or registered plumber in accordance with the applicable plumbing and backflow protection requirements in your location.

For Australia, installation should comply with the Plumbing Code of Australia and relevant local requirements. For New Zealand, installation should comply with applicable New Zealand Building Code and local plumbing requirements.

Any electrical work, if required, should be carried out by a licensed electrician or authorised electrical worker.




Incorrect installation may cause water leakage, product malfunction, or injury, and may affect warranty coverage.

※ Precautions before installation

- 1、 Before installation, toilet wall, floor tile, ceramic toilet has been completed, bathroom should supply water and power socket near by toilet.
- 2、 Water pressure should be between 0.08Mpa(flow)-0.75MPa (Static),water temperature 5℃-35℃.
- 3、 In case of the remain water within frozen,please put the product in a warm place wait to thaw then install it.
- 4、 Connect daily-use water pipe only.
Do not connect to recycled water or industrial water supplies.
Due to possible contamination as this would cause jamming or internal damage.
- 5、 Please be sure to use incidental T valve and filter.
- 6、 Don't put the power plug into the socket before finishing installation.

※ Install T valve filter

- 1、 Lock inlet valve to remove water pipe. See Picture 1.
- 2、 Connect T valve, filter and inlet valve. See picture 2.
- 3、 Install flush tank and inlet pipe. See picture 3.




◆ Toilet Seat installation ◆

※ Remove original toilet seat

1.Wrench loosen bolt

2.Remove the nut and gasket, remove the toilet seat




※ Install fix bracket

1.Before the installation, please put the product on the toilet bowl to check the fitness.

2.Embed and install the rubber sleeve, fix bracket, metal bracket in the picture shown, insert the mounting bolt and tighten it so that the fix bracket cannot move.


3.If the product does not match the toilet bowl ideally, please loosen the mounting bolts, take the metal gasket out, readjust the position of the fix bracket, then insert the metal gasket and tighten the bolt.



※ The fix bracket can adjust the range within 120-180mm

※ Install bidet

Aim the bottom card slot of the seat to the edge of fixed bracket, slide in gently, as you hear 'ka' sound means well installed



※ Notice: please don't forget the power cable between the toilet and bidet.

Be sure the bidet fixed as complete then lift bidet to fit it on correct position.


※ Connect inlet pipe

Connect T valve

Hold on PE Inter to push it towards connector of T valve.

Connect bidet

Hold on PE inter to push it towards connector of bidet.




※ It is recommended to replace the PE pipe every year

※ Turn on inlet valve after connected, please check the connector part leakage or not.

Operation

◆ Operation introduction


※ The following illustrations are for functional descriptions only, the full light state is not the actual state.




Control panel

◆ Preparation

1. Open the water-inlet valve



2. Ensure the plug is inserted into socket and the indicator light is on.



3. Confirm the power icon in LED display is on



4. If the power light on the product indicator panel is not lit, all functions will be unavailable, please press the power button on the operation button panel.



◆ How to use

Sit on the seat

Seated-sensor activated

The deodorization function runs automatically when the deodorization function is turned on. Functions such as rear wash/front wash/dry must be seated to use.

Front wash

Press , nozzle reaches out to work; Press again change to front oscillating cleansing, nozzle repeatedly swings back or front. Press again to stop oscillating cleansing, Switch back to front wash.

Water pressure adjustment

4-level for choosing, adjust comfortable water pressure by pressing

 Weak
 Strong 



Stop



Rear wash




Front wash



Dryer



Nozzle clean



Rear wash

Press , nozzle reaches out to work; Press again change to rear oscillating cleansing, nozzle repeatedly swings back or front. Press again, stop oscillating cleansing. Switch back to rear wash.

Nozzle position adjustment

4-level for adjusting the satisfied position to clean by pressing  Back .

Notice: Under oscillating cleaning, the nozzle position adjustment is unavailable.

Stop

Stop the current cleaning operation. If do not press stop button, rear washing/ front washing will stop automatically after 2minutes.

Dryer

Press this button to start warm air drying.

Warm air temp adjustment

4-level for choosing, adjust warm air temp by pressing $\begin{matrix} + & \text{Weak} \\ \text{Strong} & - \end{matrix}$.



Stop



Rear wash



Front wash



Dryer



Nozzle clean



Stop

Turn off the drying function. Or the warm air will stop automatically after running for 4 minutes.

Nozzle clean

Press  to enter nozzle cleaning, then water flows out and you can clean the nozzle. Press the stop button to end immediately.

※Nozzle clean is effective when people are not seated.


※Nozzle will automatically clean the peripheral part of the nozzle before rear wash and front wash.

Night light

Press this button to turn on/off the night light function, the indicator on the control panel turns on/off synchronously with the on/off the function.

Power

Press this button to turn off the power.
Press any buttons to turn on.



Deodorizer

Press this button to turn on/off the deodorization function, the indicator on the control panel turns on/off synchronously with the on/off the function.

- ※Deodorization function continue working 1.5 minutes after sensing off seat, then auto stop.
- ※The deodorizer function temporarily stops during drying, and starts automatically after drying.

Power saving

Press this button to turn on/off the power saving function, the indicator on the control panel turns on/off synchronously with the on/off the function.

When the power saving function is turned on, the seat temperature will be lowered and maintained at 25°C after a person leaves the seat for 1.5 minutes.


Seat temp adjustment

Press this button to enter seat temp adjustment. 4-level for choosing, Normal temp, 1 level, 2 level, 3 level. Normal temp are not heating; 1 level is 33 °C, 1 light on; 2 level is 36 °C, 3 lights on; 3 level is 39 °C, 5 lights on. With each push, seat temp change to the next level.

Attention: To prevent the low temp scalding, the toilet seat will automatically lowered to below 35 °C after sit on the seat for 10 minutes.

Water temp adjustment

Press this button to enter water temp adjustment. 4-level for choosing, Normal temp, 1 level, 2 level, 3 level. Normal temp are not heating; 1 level is 33 °C, 1 light on; 2 level is 36 °C, 3 lights on; 3 level is 39 °C, 5 lights on. With each push, water temp change to the next level.



Strong wash

In idle mode, press and hold this button to enter powerful wash mode at idle mode, the nozzle is stretched out work, hole starts sewage. The water pressure is highest level, after washing there are 2 minutes to finish. Press  to end.

Buzzer

Buzz once: Sit on seat condition, all the functions are available.

Buzz twice: Off the seat condition, parts of the functions are available.

Buzz three times or more: There are faults of the product.

Reminder

Buzzer only works when operate on remote controller or side button or initialization.

◆ Trouble shooting ◆

SITUATION	REASON	PROCESS
No power	The electrical outlet is not connect to power supply or the plug is not insert to the bottom	Check if the electrical outlet is connected to the power supply; press the reset key on the plug
No water comes out while cleaning	Low pressure of water supply	Raise the water pressure
	Water inlet filter blocked	Remount and clean the filter according to the instruction
Cleansing water in not warm enough	Water temp setting is incorrect	Readjust
Seat does not heat	Seat temp setting is incorrect or the product is in power saving mode	Readjust
Seat and cover are loose	Fixed bolts are loose	Tighten the bolts
No response when pressing the key	Key fault	Reboot or contact ascendant

Cleaning and Maintenance


● Toilet bowl cleaning

- ◆ Please make sure the electrical plug is taken out
- ◆ Please use wet soft cloth to wipe the toilet shelf and seat.
The dirt should be cleaned as soon as possible, if it's difficult to clean, you can use neutral detergent.


● Nozzle Cleaning and Maintenance

- ◆ Press "nozzle clean", nozzle will come out and start auto wash, then you can use brush to clean it.

Attention:
Do not use steel brush to clean



● Machine release



When the whole machine needs to be detached, press the Release button while holding the whole machine and pull it back forcefully.

• Cleaning the filter


When the water pressure is too low or insufficient, please clean the filter.

1

Close the T valve filter and stop water supply

Notice: Do not remove the filter without closing the T valve filter.

—Otherwise water will spray out




2

Remove the T valve filter

unscrew the connector by spanner and then take out the filter.

For the specific operation, see the figure below:



3

Clean the filter


Get the filter out and clean it thoroughly.

-----Flush off dirt or clean the filter by toothbrush

Notice: Do not use any cleaning agents.

Clean it with water only.

Do not use excessive force when cleaning, otherwise the filter will be deformed or damaged, affecting normal use.



4

Reattach the filter

Reinstall filter based on the removal sequence.

Notice: Open the shutoff valve after installation and confirm there's no water leakage.

Appendix

◆ Product specification ◆

Ambient temp range		4℃-40℃
Inlet water temp range		5℃-35℃
Rated voltage		220V~ 50Hz
Rated power		1200W
Power cord length		1.5m
Cleansing device	Water pressure range	0.08MPa-0.75MPa
	Water pressure adjustment	Adjustable in 4 levels
	Water temp adjustment	4 levels adjust: Room temp, 33℃, 36℃, 39℃
	Safety device	Temp sensor control system、Dry burning-resistant protection device、over temp protection system、water and electricity isolation system
	Rear wash	0.4-0.6 L/min(water pressure $\geq$ 0.15MPa)
	Front wash	0.4-0.65 L/min(water pressure $\geq$ 0.15MPa)
	Strong wash	0.45 L/min(water pressure $\geq$ 0.15MPa)
Seat heating device	Seat temp control	4 levels adjust: Room temp, 33℃, 36℃, 39℃
	Seat protective system	Temperature sensing control system/ fuse
Warm air dryer	Warm air temperature	4 levels adjustable: 35℃, 42℃, 48℃, 54℃ (The wind temp is greatly affected by the environment, and the values are for reference only.)
	Safety device	Temperature reset switch/fuse
Deodorizer		Catalyst deodorant box

◆ Packing list ◆

Dear User:

Please check whether the products are complete after you open the box of toilet.

Product packaging box containing the items are:

1 smart bidet seat

1 manual

1 rubber gasket

1 T-Valve with Filter

1 PE inlet pipe

1 fixing bracket

1 Filter

2 metal gaskets

2 mounting bolts

2 rubber sleeves

1 screwdriver

Warning

1. This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
2. Children should be supervised to ensure that they do not play with the appliance.
3. If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.

Distributed by Conor Australia Pty Ltd

Australia: conors.com.au

New Zealand: conors.co.nz

Support: support@conors.com.au

326D